



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

05

001MRZI

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$,
for internal and external walls and floorings**

| | |
|---|---|
| Reaction to fire | Class A1 _{FL} /A1 |
| Breaking strength | Thickness <7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1300 N |
| Slipperiness | See table attached |
| Durability, for: - Internal use - External use: Freeze/thaw resistance | Passed Passed |
| Resistance to thermal shock | Passed |



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

05

002MRZI

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $0,5% < E_b \leq 3%$,
for internal and external walls and floorings**

| | |
|---|---|
| Reaction to fire | Class A1 _{FL} /A1 |
| Breaking strength | Thickness <7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1100 N |
| Durability, for: - Internal use - External use: Freeze/thaw resistance | Passed Passed |
| Resistance to thermal shock | Passed |



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

05

003MRZI

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $3% < E_b \leq 6%$,
for internal walls and floorings**


| | |
|------------------------------------|---|
| Reaction to fire | Class A1 _{FL} /A1 |
| Breaking strength | Thickness <7,5 mm Breaking strength ≥ 600 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1000 N |
| Durability, for: - Internal use | Passed |


| | |
|--|----------|
| CE | |
| Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) | |
| 05 004MRZI | |
| EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $6% < E_b \leq 10%$, for internal walls | |
| Reaction to fire | Class A1 |
| Durability, for: - Internal use | Passed |

| | |
|--|----------|
| CE | |
| Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) | |
| 05 005MRZI | |
| EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b > 10%$, for internal walls | |
| Reaction to fire | Class A1 |
| Durability, for: - Internal use | Passed |

| | |
|---|----------|
| CE | |
| Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) | |
| 05 006MRZI | |
| EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $3% < E_b \leq 6%$, for internal walls | |
| Reaction to fire | Class A1 |
| Durability, for: - Internal use | Passed |

| | |
|--|--|
| CE | |
| Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) | |
| 05 007MRZI | |
| EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b > 10%$, for internal walls and floorings | |
| Reaction to fire | Class A1 _{FL} /A1 |
| Breaking strength | Thickness <7,5 mm Breaking strength ≥ 200 N Thickness $\geq 7,5$ mm Breaking strength ≥ 600 N |
| Durability, for: - Internal use | Passed |

| | |
|--|---|
|  | |
| <p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>008MRZI</p> | |
| <p>EN 14411:2012</p> <p>Extruded ceramic tiles, with water absorption $E_b \leq 0,5\%$, for internal and external walls and floorings</p> | |
| Reaction to fire | Class A1 _{FL} /A1 |
| Breaking strength | Thickness <7,5 mm Breaking strength ≥ 600 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1300 N |
| Durability, for: | |
| - Internal use | Passed |
| - External use: Freeze/thaw resistance | Passed |
| Resistance to thermal shock | Passed |

| | |
|---|----------|
|  | |
| <p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</p> <p>05</p> <p>009MRZI</p> | |
| <p>EN 14411:2012</p> <p>Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$, for internal and external walls</p> | |
| Reaction to fire | Class A1 |
| Durability, for: | |
| - Internal use | Passed |
| - External use: Freeze/thaw resistance | Passed |
| Resistance to thermal shock | Passed |



**Marazzi Group s.r.l. a socio unico,
Viale Regina Pacis 39
41049 Sassuolo (MO)**

05

010MRZI

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $0,5% < E_b \leq 3%$,
for internal and external walls and floorings**

| | |
|---|------------------|
| Reaction to fire | Class A1 |
| Durability, for: - Internal use - External use: Freeze/thaw resistance | Passed Passed |
| Resistance to thermal shock | Passed |