

FLOORS 20 MM

Uniche20



MARAZZI



Uniche20

Uniche20 brings the natural appeal of Mediterranean stone outdoors with the 60x120 cm format in 20 mm porcelain stoneware, ideal for terraces, pathways, and gardens. Available in four colours — Ostuni, Cadiz, Arles and Avignone — the collection combines material realism and durability, offering both a technical and aesthetic solution for any outdoor space.

MAS5 Uniche20 Arles Str Elemento Ad L Rt 15x120cm
MAR6 Uniche20 Arles Rt 60x120cm
M9EG Oltre Natural Grip Rt 20x120cm




Uniche20 Index

MAS5 Uniche20 Arles Str Elemento Ad L Rt 15x120cm
MAR6 Uniche20 Arles Rt 60x120cm
M9EG Oltre Natural Grip Rt 20x120cm

Uniche20

- Colorbody Fine Porcelain Stoneware




Arles

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MAR6	Uniche20 Arles Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	3D Ink, StepWise	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V4	1	0,72	32,45	36	25,92	1.168,09




Avignone

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MAR7	Uniche20 Avignone Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	3D Ink, StepWise	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V4	1	0,72	31,96	36	25,92	1.150,47



Cadiz

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MAR5	Uniche20 Cadiz Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	3D Ink, StepWise	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V4	1	0,72	32,03	36	25,92	1.153,02



Ostuni

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MAR4	Uniche20 Ostuni Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	3D Ink, StepWise	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V4	1	0,72	32,42	36	25,92	1.167,04

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni



ISO 14001



Greenguard Certification



CAM Sassuolo



ISO 9001



LEED Credits



CCC



Green Building Council



QBUPEC F+



CE 001MRZI



GPP



FDES



UKCA 001MRZUK



EPD Italy



Declare



SASO



ISO 17889-1



HPD

© Copyright by Marazzi Group S.r.l., 2023.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI