

FLOORS 20 MM

Slow20



MARAZZI



Slow20

With Slow20, the charm of traditional terracotta extends outdoors through a 20mm-thick porcelain stoneware surface that combines beauty and functionality. Available in the 80x80 cm format and in the colours Calce, Sabbia, Cotto, and Coccio, it expresses the genuine beauty of natural earth while ensuring durability, strength, and aesthetic continuity in outdoor spaces.

MGUS Artcraft Argilla Struttura 3D Bande 20x20cm
MGRG Slow20 Sabbia Rt 80x80cm
MFKM Slow Sabbia Rt 120x120cm





Slow20 Index

MGUS Artcraft Argilla Struttura 3D Bande 20x20cm
MGRG Slow20 Sabbia Rt 80x80cm
MFKM Slow Sabbia Rt 120x120cm

Slow20

- Colorbody Fine Porcelain Stoneware



Calce

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
80x80cm	Structured Surface	MGR9	Slow20 Calce Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2	1	0,64	27,89	45	28,80	1.254,90



Coccio

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
80x80cm	Structured Surface	MGRX	Slow20 Coccio Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2	1	0,64	28,31	45	28,80	1.273,77



Cotto

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
80x80cm	Structured Surface	MGS0	Slow20 Cotto Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2	1	0,64	28,14	45	28,80	1.266,49



Sabbia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
80x80cm	Structured Surface	MGRG	Slow20 Sabbia Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2	1	0,64	28,50	45	28,80	1.282,28

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni



ISO 14001



Greenguard Certification



CAM Sassuolo



ISO 9001



LEED Credits



CCC



Green Building Council



QBUPEC F+



CE 001MRZI



GPP



FDES



UKCA 001MRZUK



EPD Italy



Declare



SASO



ISO 17889-1



HPD

© Copyright by Marazzi Group S.r.l., 2023.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI