

CONTRACTORS FLOORS

Progress


MARAZZI

Progress

Progress by Marazzi repropose the charm of cement floor tiles with a collection of simple, clean-lined ceramic tiles. Its natural, lightly colour-shaded surfaces and neutral colours lend sobriety and elegance to spaces. Marazzi's Progress collection is in porcelain stoneware and features traditional square tiles complemented by decorative insert tiles with subtle metallic effects. The collection has been designed for the walls and floors of interior design projects for any domestic setting, particularly day areas and bathroom and kitchen environments.



Progress Index




Anthracite

Progress


- Porcelain Stoneware

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x60cm	Natural	MKL6	Progress Anthracite Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				F	V1	3	1,08	20,71	40	43,20	828,38
30x60cm	Natural	MKSY	Progress Anthracite Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				F	V1	6	1,08	20,78	48	51,84	997,31




Beige

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
33,3x33,3cm	Natural	MJMH	Progress Beige 33,3x33,3	MM 08	.	Frost proof, Resistance deep abrasion	Floor & Wall										16	1,77	30,49	38	67,42	1,158,44
60x60cm	Natural	MKL2	Progress Beige Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				G	V1	3	1,08	21,14	40	43,20	845,73
30x60cm	Natural	MKSU	Progress Beige Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				G	V1	6	1,08	20,81	48	51,84	998,84
45x45cm	Natural	ML9S	Progress Beige	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall										5	1,01	19,65	33	33,41	648,53



Gray

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x60cm	Natural	MKL5	Progress Gray Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				G	V1	3	1,08	20,67	40	43,20	826,79
30x60cm	Natural	MKSX	Progress Gray Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				G	V1	6	1,08	20,52	48	51,84	984,99



Hazelnut

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x60cm	Natural	MKL3	Progress Hazelnut Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				G	V1	3	1,08	20,99	40	43,20	839,65
30x60cm	Natural	MKSV	Progress Hazelnut Rt	MM 8,5	.	Frost proof, Resistance deep abrasion	Floor & Wall				Class 1				G	V1	6	1,08	20,85	48	51,84	1,000,58

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour























V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni

					
ISO 14001	ISO 50001	ISO 45001	ISO 9001	Green Building Council	GPP
					
EPD Italy	ISO 17889-1	Greenguard Certification	LEED Credits	QBUPEC	FDES
					
Declare	HPD	CAM Sassuolo	CAM Fiorano	CCC	CE 001MRZI
					
CE 010MRZ	UKCA 001MRZUK	UKCA 010MRZUK	SASO		

© Copyright by Marazzi Group S.r.l., 2023.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI